Safety Data Sheet



Page 1/5 Printing date 09/14/2016 Revision date 09/13/2016

Revision date 09/13/2016
1 Identification
Product identifier
Product name: Bismuth(III) telluride, Vacuum Deposition Grade
Stock number: 14519 CAS Number:
1304-82-1 EC number:
215-135-2 Relevant identified uses of the substance or mixture and uses advised against. Identified use: SU24 Scientific research and development
Details of the supplier of the safety data sheet
Alfa Aesar Thermo Fisher Scientific Chemicals, Inc.
30 Bond Street Ward Hill, MA 01835-8099
Tel: 800-343-0660 Fax: 800-322-4757
Email: tech@alfa.com www.alfa.com
Information Department: Health, Safety and Environmental Department Emergency telephone number:
During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.
2 Hazard(s) identification
Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)
CHS07
Acute Tox. 4 H302 Harmful if swallowed.
Acute Tox. 4 H312 Harmful in contact with skin.
Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation. Hazards not otherwise classified No information known.
Label elements GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS) Hazard pictograms
GHS07
Signal word Warning Hazard statements
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled. H315 Causes skin irritation.
H319 Causes serious eye irritation.
Precautionary statements
P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection.
P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P362 Take off contaminated clothing and wash before reuse. P363 Wash contaminated clothing before reuse.
P321 Specific treatment (see on this label). P405 Store locked up.
P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
WHMIS classification D1B - Toxic material causing immediate and serious toxic effects D2B - Toxic material causing other toxic effects
Classification system
HMIS ratings (scale 0-4) (Hazardous Materials Identification System)
HEALTH 2 IPRE 0 Flammability = 0 REACTIVITY Physical Hazard = 1
Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.
3 Composition/information on ingredients
Chemical characterization: Substances
CAS# Description: 1304-82-1 Bismuth(III) telluride
(Contd. on page 2)

(Contd. on page 2)

Product name: Bismuth(III) telluride, Vacuum Deposition Grade

Identification number(s): EC number: 215-135-2

4 First-aid measures

Description of first aid measures

Description of first aid measures After inhalation Supply fresh air. If required, provide artificial respiration. Keep patient warm. Seek immediate medical advice. After skin contact Immediately wash with water and soap and rinse thoroughly. Seek immediate medical advice. After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor. After swallowing Seek medical treatment. Information for doctor Most important symptoms and effects, both acute and delayed Causes skin irritation. Harmful if swallowed. Causes serious eve irritation. Causes serious eye irritation. Harmful if inhaled. Harmful in contact with skin. May cause respiratory irritation. **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

Extinguishing media **Suitable extinguishing agents** Product is not flammable. Use fire-fighting measures that suit the surrounding fire. **Special hazards arising from the substance or mixture** If this product is involved in a fire, the following can be released: Tellurium dioxide (TeO2) Pirmuth evide Bismuth oxide

Bismuth oxide Advice for firefighters Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away Ensure adequate ventilation Ensure adequate ventilation Environmental precautions: Do not allow product to reach sewage system or any water course. Methods and material for containment and cleaning up: Dispose of contaminated material as waste according to section 13. Ensure adequate ventilation. Prevention of secondary hazards: No special measures required. Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for disposal information. 7 Handling and storage ndli

nanaling			
Precautions	for cofe	handling	
FIECAULIONS	IUI Sale	nanunnu	

Interactions for sale nanoing Handle under dry protective gas. Keep container tightly sealed. Store in cool, dry place in tightly closed containers. Ensure good ventilation at the workplace. Information about protection against explosions and fires: The product is not flammable Conditions for safe storage, including any incompatibilities Storage Requirements to be met by storerooms and receptacles: No special requirements. Information about storage in one common storage facility: Store away from water/moisture. Do not store together with acids. Store away from oxidizing agents. Further information about storage conditions: Store under dw. inert as Store under dry inert gas. This product is moisture sensitive. Keep container tightly sealed. Store in cool, dry conditions in well sealed containers. Protect from humidity and water. Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Control parameters

Components	with limit values that require monitoring at the workplace:	
1304-82-1 Bi	smuth(III) telluride (100.0%)	
	Long-term value: 15* 5** mg/m ³ undoped *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** 5*** mg/m ³ undoped :*total dust, **resp.fract.; ***Se-doped	
TLV (USA)	Long-term value: 10* 5** mg/m ³ *undoped **Se-doped	
EL (Canada)	Long-term value: 5* 10** mg/m³ *Se-doped;**undoped	
	(Contd)	on page 3)

USA -

(Contd. of page 1)

EV (Canada) Long-term value: 10 5* mg	(Contd. of pa	
	//m ³	age 2)
*selenium-doped		
Recommended inter device for short t Use a respirator with type P100 (USA) or purifying respirators are appropriate. On Protection of hands: Impervious gloves Check protective gloves prior to each use	andling chemicals should be followed. nd feed. hing immediately. d of work. orking environment. oirator when high concentrations are present. erm use: r93 (EN 143) cartridges as a backup to engineering controls. Risk assessment should be performed to determine if air- ly use equipment tested and approved under appropriate government standards. e for their proper condition. depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.	-
9 Physical and chemical properties	<u> </u>	
Information on basic physical and che	emical properties	
General Information Appearance:		
Form: Odor:	Various forms (powder/flake/crystalline/beads, etc.) Odorless Not determined	
Odor threshold: pH-value:	Not determined. Not applicable.	
Change in condition Melting point/Melting range: Boiling point/Boiling range: Sublimation temperature / start: Flammability (solid, gaseous) Ignition temperature: Decomposition temperature: Auto igniting:	573 °C (1063 °F) Not determined Not determined Not determined Not determined Not determined Not determined Not determined	
Danger of explosion: Explosion limits: Lower: Upper: Vapor pressure: Density at 20 °C (68 °F): Relative density	Not determined. Not determined Not applicable. 7.642 g/cm³ (63.772 lbs/gal) Not determined.	
Vapor density Evaporation rate Solubility in / Miscibility with Water: Partition coefficient (n-octanol/water): Viscosity: dynamic:	Not applicable. Not applicable. Decomposes	
kinematic: Other information	Not applicable. Not further relevant information available.	
10 Stability and reactivity Reactivity No information known. Chemical stability Stable under recomm Thermal decomposition / conditions to Possibility of hazardous reactions Re- Conditions to avoid No further relevant Incompatible materials: Acids Water/moisture Oxidizing agents Hazardous decomposition products: Tellurium dioxide (TeO2) Bismuth oxide	o be avoided: Decomposition will not occur if used and stored according to specifications. acts with strong oxidizing agents	
Specific target organ system toxicity -	in irritation. ious eye irritation. wn. wn. carcinogen: Inadequate data on which to classify the agent in terms of its carcinogenicity in humans and/or animals. n.	age 4)

Safet	/ Data	Sheet
acc. to	OSHA H	CS

Product name: Bismuth(III) telluride, Vacuum Deposition Grade		
Subacute to chronic toxicity: No effects known. Additional toxicological information: To the best of our knowledge the acute Carcinogenic categories OSHA-Ca (Occupational Safety & Health Administration) Substance is not		(Contd. of page 3)
12 Ecological information Toxicity Aquatic toxicity: No further relevant information available. Persistence and degradability No further relevant information available. Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available. Additional ecological information: General notes: Do not allow undiluted product or large quantities to reach ground water, water Avoid transfer into the environment. Results of PBT and vPvB assessment PBT: Not applicable.	^r course or sewage system.	
vPvB: Not applicable. Other adverse effects No further relevant information available.		
13 Disposal considerations Waste treatment methods Recommendation Consult state, local or national regulations to ensure proper Uncleaned packagings: Recommendation: Disposal must be made according to official regulations.	r disposal.	
14 Transport information		
UN-Number DOT, IMDG, IATA	UN3284	
UN proper shipping name DOT IMDG, IATA	Tellurium compound, n.o.s. (Bismuth(III) telluride) TELLURIUM COMPOUND, N.O.S. (Bismuth(III) telluride)	
Transport hazard class(es) DOT		
Class Label Class Label IMDG, IATA	6.1 Toxic substances. 6.1 6.1 (T5) Toxic substances 6.1	
Class Label	6.1 Toxic substances. 6.1	
Packing group DOT, IMDG, IATA	III	
Environmental hazards:	Not applicable.	
Special precautions for user EMS Number:	Warning: Toxic substances F-A,S-A	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Cod		
Transport/Additional information:		
DOT Marine Pollutant (DOT):	No	
UN "Model Regulation":	UN3284, Tellurium compound, n.o.s. (Bismuth(III) telluride), 6.1, III	
15 Pagulatory information		
 15 Regulatory information Safety, health and environmental regulations/legislation specific for the s GHS label elements The product is classified and labeled in accordance with Hazard pictograms GHS07 Signal word Warning Hazard statements H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H35 May cause respiratory irritation. Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/fa P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minuted. P362 Take off contaminated clothing and wash before reuse. P363 Wash contaminated clothing before reuse. P361 Specific treatment (see on this label). 	29 CFR 1910 (OSHA HCS)	

Product name: Bismuth(III) telluride, Vacuum Deposition Grade

(Contd. of page 4) P405 P403+P233 P501 Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. National regulations All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory. All components of this product are listed on the Canadian Non-Domestic Substances List (NDSL). SARA Section 313 (specific toxic chemical listings) Substance is not listed. California Proposition 65 Prop 65 - Chemicals known to cause cancer Substance is not listed. Prop 65 - Developmental toxicity Substance is not listed. Prop 65 - Developmental toxicity, male Substance is not listed. Prop 65 - Developmental toxicity, male Substance is not listed. Prop 65 - Developmental toxicity, and E Substance is not listed. Information about limitation of use: For use only by technically qualified individuals. Other regulations, limitations and prohibitive regulations Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed. The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed. market and use must be observed. Substance is not listed. Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed. Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. Conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the use Department issuing SDS: Global Marketing Department Date of preparation / last revision 09/14/2016 / - Abbreviations and acronyms:
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods by Road)
 DT: US Department of Transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DT: US Department of Transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Air Transport Association
 ENIECS: European Inventory of Existing Commercial Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 HMIS: Hazardous Materials Information System (USA)
 WHMIS: Workplace Hazardous Materials Information System (Canada)
 LCSO: Lethal concentration, 50 percent
 UPVB: very Persistent and very Bioaccumulative
 ACGIH: American Conference of Governmental Industrial Hygienists (USA)
 OSHA: Occupational Safety and Health Administration (USA)
 MARC: International Agerocy for Research on Cancer
 EPA: Environmental Protection Agency (USA)
 Acute Tox: 4. Acute toxicity, Hazard Category 2
 Eyn Imt: 2X: Serious eye damage/eye irritation, Hazard Category 2A
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

USA