EREZTECH LLC



11555 Medlock Bridge Road, Suite 100, Johns Creek, GA 30097, USA

T: +1.888.658.1221 F: 1.678.619.2020

E: info@ereztech.com W: http://ereztech.com

SAFETY DATA SHEET

Section 1. Identification

Product Name: Tantalum(V) chloride anhydrous

Product Type: Solid

CAS Number: 7721-01-9 **Product Number:** <u>TA1019</u>

Product Manufacturer: Ereztech LLC

11555 Medlock Bridge Road, Suite 100

Johns Creek, GA 30097

Product Information: (888) 658-1221

In Case of an Emergency: CHEMTREC: 1-800-424-9300 (USA);

+1 703-527-3887 (International); CCN836180
*** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Appearance/Odor: Off-white powder, odor not determined.

Classification: ACUTE TOXICITY, ORAL – Category 4, H302

SKIN CORROSION/IRRITATION - Category 1B, H314

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1, H318 SPECIFIC TARGET ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY TRACT IRRITATION - Category 3, H335

GHS Label Elements

Hazard Pictograms:



Signal Word: DANGER

Hazard Statements: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage. H335: May cause respiratory irritation.

Precautionary statements

Prevention: P260: Do not breathe dusts or mists.

P264: Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

<u>Ereztech TA1019</u> Page 1 of 13 Revision: 1.00
Date of Issue: 3/19/2020

Section 2. Hazards Identification

Prevention (cont.): P271: Use only outdoors or in well-ventilated area.

P280: Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response: P301 + P312: IF SWALLOWED: Call a POISON CENTER or

doctor/physician if you feel unwell.

P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do not

induce vomiting.

P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take off

immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340: IF INHALED: Remove victim to fresh air and keep at

rest in a position comfortable for breathing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue

rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P330: Rinse mouth.

P363: Wash contaminated clothing before reuse.

P403 + P233: Store in a well ventilated place. Keep container

tightly closed.

P405: Store locked up.

P501: Dispose of contents/ container to an approved wasted

disposal plant.

OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Hazards Not Otherwise None identified.

Classified (HNOC):

Section 3. Composition/Information on Ingredients

Substances

Storage:

Disposal:

Formula : TaCl₅

Synonyms : Tantalum pentachloride.

Molecular Weight: 358.21 g/molCAS-No.: 7721-01-9

Ingredient Name	%	CAS Number
Tantalum(V) chloride anhydrous	≥ 98	7721-01-9

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

General Advice: Move out of dangerous area. Call a physician or POISON CONTROL CENTER

immediately. Show this safety data sheet to the doctor in attendance.

Eye Contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and

lower eyelids. Check for and remove any contact lenses. Continue rinsing. Call

a POISON CENTER or doctor/physician immediately.

Skin Contact: Take off contaminated clothing and shoes immediately. Wash off contaminated

skin with soap and plenty of water. Call a POISON CENTER or doctor/physician

immediately.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband. Call a POISON CENTER or doctor/physician immediately.

Ingestion: Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting

occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in

recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a

physician or POISON CONTROL CENTER immediately.

Most Important Symptoms/Effects, Acute And Delayed Potential Acute Health Effects

Eye Contact: Causes severe eye damage. Symptoms may include itching, watering and

redness, severe pain and temporary/permanent loss of vision.

Inhalation: Symptoms may include burning/itching sensation in sinuses and throat,

coughing, shortness of breath, difficulty in breathing, nausea and headaches.

Skin Contact: Product is corrosive to skin. Symptoms may include burning, itching, pain,

redness, blistering and tissue necrosis.

Ingestion: Compounds released when product is exposed to moisture/water may be

expected to be corrosive to mucous membranes and tissues of the mouth, esophagus and digestive tract. Symptoms may include burning, nausea,

vomiting and abdominal pain.

Chronic Symptoms:

None identified.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: Treat symptomatically.

Specific Treatments: No specific treatment.

Section 4. First Aid Measures

Protection of First Responders:

No action taken shall be taken involving any personal risk without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See Toxicological Information (Section 11)

Section 5. Fire Fighting Measures

General Hazards: Product reacts with water to release hydrogen chloride.

Suitable Extinguishing Media: THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY

CHEMICAL POWDER PRESSURIZED WITH NITROGEN.

Vermiculite, sand, dry chemical or carbon dioxide (CO₂) may

also be used.

None identified.

Unsuitable Extinguishing Media: DO NOT USE WATER OR FOAM as product reacts to produce

hydrogen chloride gas.

Unusual Fire and Explosion Hazards:

Product of Combustion: Hydrogen chloride and tantalum oxides.

Protection of Firefighters: Promptly isolate the scene by removing all persons from the

vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Avoid contact with skin or eyes. Avoid the formation and inhalation of dusts, aerosols, vapors and gases.

Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full

face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep

unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid the formation and inhalation of dusts, aerosols, vapors, and gases. Provide adequate ventilation. Wear respiratory protection. Put on

appropriate personal protective equipment.

For Emergency Responders: If specialized clothing is required to deal with the spillage, take

note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency

personnel".

Ereztech TA1019 Page 4 of 13 Revision: 1.00

Section 6. Accidental Release Measures

Environmental Precautions:

Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for Containment

General: Move containers from spill area if safe to do so. Avoid the

formation and inhalation of dusts, aerosols, vapors and gases.

Small Spill: Contain and collect spillage with a dry, binding material (e.g.

sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal

contractor.

Large Spill: Approach release from upwind. Prevent entry into sewers,

water courses, basements or confined areas. Contain and collect spillage with a dry, binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the

same hazard as the spilled product.

Note: see Section 1 for emergency contact information and

Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions: Product is moisture sensitive; handle under a dry, inert gas.

Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Avoid formation and inhalation of dusts and aerosols. Keep container tightly sealed. Avoid contact with skin, eyes and clothing. Do not ingest. Avoid prolonged

exposure. Ensure adequate ventilation.

Protective Measures: Put on appropriate personal protective equipment (see Section

8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be

hazardous. Do not reuse container.

General Occupational Hygiene: Eating, drinking and smoking should be prohibited in areas

where this material is handled, stored and processed. Workers

should wash hands and face before eating, drinking or

smoking.

Section 7. Handling and Storage

General Occupational Hygiene: (cont.)

Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safe Storage Conditions:

Product is moisture sensitive; store under an inert gas.

Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials noted above and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Occupational Exposure Limits:

Product contains no substances with occupational exposure limit values.

Engineering Controls:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures:

Avoid all unnecessary exposure. Wash all exposed skin (hands, forearms and face) thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do not inhale dusts, aerosols, vapors or gases. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure Controls/Personal Protection

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to dusts, aerosols, vapors or sprays. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Skin Protection Hand Protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. For full contact, use Neoprene or nitrile rubber.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State: Solid.

Color: Off-white.

Odor: No data available.
Odor Threshold: No data available.
pH: No data available.
Melting Point: 221 °C (429.8 °F).

Boiling Point: 242 °C (467.6 °F) @ 760 mmHg.

Flammability: Non-flammable.

Relative Density: 3.68 g/cm³ @ 25 °C (77 °F).

Vapor Pressure: No data available.
Vapor Density: No data available.

Water Solubility: 0.396 mg/L @ 20 °C (68 °F).

Section 10. Stability and Reactivity

Reactivity:This product reacts with water and compounds containing active hydrogen such as alcohols and acids to produce

hydrogen chloride.

Chemical Stability: This product is stable when stored under a dry, inert

atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air is recommended.

Conditions to Avoid: Exposure to water/moisture.

Incompatible Materials: Water, compounds containing active hydrogen (alcohols,

acids) and strong oxidizing agents.

Hazardous Decomposition Products: In contact with water, product reacts to produce

hydrogen chloride. Hazardous decomposition products formed under fire conditions: hydrogen chloride and tantalum oxide fumes. In the event of a fire: see section

5.

Possibility of Hazardous Reactions: Under normal conditions of storage and use noted above,

hazardous reactions will not occur. Hazardous reactions or instability may occur under certain conditions of storage or use. In contact with water, product releases

hydrogen chloride.

Section 11. Toxicological Information

Information on Toxicological Effects

Acute Toxicity

Component	CAS No	Result	Species	Dose	Exposure
Tantalum chloride	7721-01-9	LD50 Oral	Rat	1900 mg/kg	-

: No specific data available.

: No specific data available.

Irritation/Corrosion

: In vitro study: corrosive – 4h (OECD Test Guideline

431).

Sensitization

Germ Cell Mutagenicity

Carcinogenity

IARC

: No component of this product present at levels greater

than 0.1% is identified as probable, possible or

confirmed human carcinogen by IARC.

ACGIH

NTP

OSHA

: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.

: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.

: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.

Reproductive Toxicity

Teratogenicity

Specific Target Organ Toxicity (Single Exposure)

Specific Target Organ Toxicity (Repeated Exposure)

Aspiration Hazard Information on the Likely

Routes of Exposure Additional Information

- : This product is not expected to cause reproductive or developmental effects.
- : No specific data available.
- : May cause respiratory irritation.
- : No specific data available.
- : No specific data available.
- : No specific data available.
- : Material is extremely destructive to tissues of the eyes, skin, mucous membranes and upper respiratory tract. If product is ingested, severe burns of the mouth and throat may be expected accompanied by the danger of perforation of the esophagus and stomach.

To the best of our knowledge, the chemical, physical and toxicological properties of this product have not been thoroughly investigated.

Ereztech TA1019 Page 9 of 13 Revision: 1.00

Section 12. Ecological Information

Numerical Measures of Toxicity

Component	CAS No	Test	Species	Dose	Exposure
Tantalum chloride anhydrous	7721-01-9	LL50 Fish	Zebra fish	> 100 mg/l*	96 h
		Semi static	Water Flea	3,0860mg/l*	48 h
		ErC50 Static	Green algae	> 2,000 mg/l*	72 h

Persistence and Degradability

Biodegradability

Bioaccumulative Potential

Mobility in Soil

Other Adverse Effects

- : No specific data available.
- : No specific data available.
- : No specific data available.
- : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13. Disposal Considerations

<u>Waste Treatment Methods</u> Product

Contaminated Packaging

- : Dispose of in accordance with local, state, and federal regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals.
- : Empty containers retain product residue (liquids, vapors and gases) and can be dangerous. Dispose of as unused product.

Section 14. Transport Information

	DOT	IMDG	IATA
UN Number	UN 3260	UN 3260	UN 3260
UN Proper Shipping Name	Corrosive solid, acidic, inorganic, n.o.s. (Tantalum pentachloride)	CORROSIVE SOLID, ACIDIC, INORGANICE, N.O.S. (Tantalum pentachloride)	Corrosive solid, acidic, inorganic, n.o.s. (Tantalum pentachloride)
Transport Hazard Classes	8	8	8
Packing Group	II	II	II
Environmental Hazards	-	-	-
Additional Information	-	EMS-No: F-A, S-B	-

<u>Ereztech TA1019</u> Page 10 of 13 Revision: 1.00 Date of Issue: 3/19/2020

Section 14. Transport Information

Special Precautions for User

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transporting in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

Section 15. Regulatory Information

TSCA (Toxic Substance Control Act):

This product is listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory).

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard (Acute toxicity – ingestion; Skin corrosion or irritation; Serious eye damage or eye irritation; Specific Target Organ Toxicity (STOT), single exposure: respiratory irritation).

Massachusetts Right to Know Components

No components are subject to Massachusetts Right to Know Act.

Pennsylvania Right to Know Components

No components are subject to Pennsylvania Right to Know Act.

New Jersey Right to Know Components

No components are subject to New Jersey Right to Know Act.

California Proposition 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Page 11 of 13 Revision: 1.00 Ereztech TA1019

Section 16. Other Information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

HMIS Rating

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

History

Date of Printing : 3/19/2020
Date of Issue/Date of Revision : 3/19/2020
Date of Previous Issue : None.

References: None available.

Abbreviations and Acronyms

ACGIH: American Conference of Governmental Industrial Hygienists.

ATE: Acute Toxicity Estimate

CAS: Chemical Abstracts Service (division of the American Chemical Society).

DOT: US Department of Transportation.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System.

IARC: International Agency for Research on Cancer.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA).

Section 16. Other Information

Abbreviations and Acronyms (cont.)

IDLH: Immediately Dangerous to Life or Health (US National Institute for Occupation Health and

Safety (NIOSH)).

IMDG: International Maritime Code for Dangerous Goods.

NFPA: National Fire Protection Association.

NIOSH: National Institute of Occupational Safety and Health.

NTP: National Toxicology Program.

OSHA: Occupational Safety and Health Administration.

PEL: Permissible Exposure Limits. REL: Recommended Exposure Limits.

SARA: Superfund Amendments and Reauthorization Act.

STOT: Specific Target Organ Toxicity. TLV: Threshold Limit Values (ACGIH).

TWA: Time Weighted Average. VOC: Volatile Organic Compound.

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Ereztech TA1019 Page 13 of 13 Revision: 1.00