

1-(4-Fluorophenyl)-2-methyl-2-aminopropane Safety Data Sheet 3730310 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/29/2016 Version: 1.0

1.1. Identification	
Product form	: Substance
Substance name	: 1-(4-Fluorophenyl)-2-methyl-2-aminopropane
CAS No	: 1200-27-7
Product code	: 3730-3-10
Formula	: C10H14FN
Synonyms	: 2-(4-Fluorobenzyl)propylamine
Other means of identification	: MFCD00082702
1.2. Relevant identified uses of the s	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sat	fety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Americ T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	ion
2.1. Classification of the substance	or mixture
Classification (GHS-US)	
Skin Corr. 1AH314 - Causes severe skirEye Dam. 1H318 - Causes serious eyeSTOT SE 3H335 - May cause respirat	e damage
Skin Corr. 1A H314 - Causes severe skir Eye Dam. 1 H318 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16	e damage
Skin Corr. 1A H314 - Causes severe skir Eye Dam. 1 H318 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	e damage
Skin Corr. 1A H314 - Causes severe skir Eye Dam. 1 H318 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements	e damage
Skin Corr. 1A H314 - Causes severe skir Eye Dam. 1 H318 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	e damage tory irritation
Skin Corr. 1A H314 - Causes severe skir Eye Dam. 1 H318 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	e damage tory irritation
Skin Corr. 1A H314 - Causes severe skir Eye Dam. 1 H318 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	e damage tory irritation : : : : : : : : : : : : : : : : : : :

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up

ote/container to acto die eal plant

	P501 - Dispose of contents/container	to an approved waste	e disposal plant
2.3. Other hazards			
No additional information available			
2.4. Unknown acute toxicity (GHS US)			
Not applicable			
SECTION 3: Composition/informat	ion on ingredients		
3.1. Substance			
Substance type	: Mono-constituent		
Name	Product identifier	%	Classification (GHS-US)
1-(4-Fluorophenyl)-2-methyl-2-aminopropane (Main constituent)	(CAS No) 1200-27-7	<= 100	Flam. Liq. 4, H227 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Full text of H-phrases: see section 16			
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
4.1. Description of first aid measures			
First-aid measures general	: In case of accident or if you feel unwe where possible). Move the affected pe		
First-aid measures after inhalation	: Remove person to fresh air and keep respiration. Get immediate medical ac		thing. If not breathing, give artificial
First-aid measures after skin contact	: Wash with plenty of soap and water. I medical advice/attention.	Remove contaminate	d clothing and shoes. Get immediate
First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.			
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.		
4.2. Most important symptoms and ef	fects, both acute and delayed		
Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.			
Symptoms/injuries after inhalation	: Material is destructive to tissue of the shortness of breath, headache, nause		s and upper respiratory tract. Cough,
4.3. Indication of any immediate medi	cal attention and special treatment neede	ed	
Treat symptomatically.			
SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxid appropriate for surrounding fire.	e. Dry powder. Water	r spray. Use extinguishing media
5.2. Special hazards arising from the	substance or mixture		
Fire hazard	: Thermal decomposition generates: Ca	arbon oxides. Hydrog	en fluoride. Nitrogen oxides.
Explosion hazard	: Risk of explosion if heated under cont containers. May form flammable/explo		
5.3. Advice for firefighters			
Firefighting instructions	: In case of fire: Evacuate area. Fight fi	ire remotely due to the	e risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective of apparatus. For further information refe		
SECTION 6: Accidental release me	easures		
6.1. Personal precautions, protective	equipment and emergency procedures		
General measures	: Evacuate unnecessary personnel. En	sure adequate air vei	ntilation. Do not breathe gas, fumes,

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1.	For non-emergency personnel	
Emergency procedures :		: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2.	For emergency responders	
Protective	e equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergen	cy procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.
6.2.	Environmental precautions	

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3.	Methods and material for conta	inment and cleaning up
For con	tainment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
Method	s for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other in	formation	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4.	Reference to other sections	

No additional information available

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.		
Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, includi	ng any incompatibilities		
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources. Air sensitive. Keep contents under inert gas.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		

SECTION 8: Exposure controls/personal protection 8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.
	a

SECTION 9: Physical and chemical properties		
9.1.	Information on basic physical and chemical properties	
Physical	state	: Liquid
Color		: No data available
Odor		: No data available
Odor thre	eshold	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8 8	3.
pН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 180 °C
Flash point	: 90 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: 167.22 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
Refractive index	: 1.495 (@ 20 °C)

SECTION 10: Stability and reactivity 10.1. Reactivity No additional information available 10.2. **Chemical stability** The product is stable at normal handling and storage conditions. Possibility of hazardous reactions 10.3. No additional information available 10.4. **Conditions to avoid** Keep away from heat, sparks and flame. 10.5. **Incompatible materials** Acids. Acid chlorides. Acid anhydrides. Carbon dioxide. Strong oxidizing agents. 10.6. Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5. **SECTION 11: Toxicological information** 11.1. Information on toxicological effects

Acute toxicity	: Not classified	
Skin corrosion/irritation	: Causes severe skin burns and eye damage.	
Serious eye damage/irritation	: Causes serious eye damage.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	: Not classified	
12/08/2016	EN (English US)	SDS ID: 3730310

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
SECTION 12: Ecological informat	ion

12.1.	Toxicity	
No additional information available		
12.2.	Persistence and degradability	
No addi	itional information available	
12.3.	Bioaccumulative potential	
No addi	itional information available	
12.4.	Mobility in soil	
No addi	itional information available	
12.5.	Other adverse effects	

No additional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.	
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional information	: Recycle the material as far as possible.	
SECTION 14: Transport information		

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT)

- DOT Packaging Non Bulk (49 CFR 173.xxx)
- DOT Packaging Bulk (49 CFR 173.xxx)

DOT Symbols

DOT Special Provisions (49 CFR 172.102)

- : UN2735 Amines, liquid, corrosive, n.o.s., 8, III
- : UN2735
- : Amines, liquid, corrosive, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- : III Minor Danger
- : 203

: 241

- : G Identifies PSN requiring a technical name
- : IB3 Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal...... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27)

12/08/2016

Safety Data Sheet

DOT Quantity Limitations Cargo aircraft o CFR 175.75)	nly (49 : 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 52 - Stow "separated from" acids
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 2735
Proper Shipping Name (IMDG)	: AMINES, LIQUID, CORROSIVE, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 2735
Proper Shipping Name (IATA)	: Amines, liquid, corrosive, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: III - Minor Danger

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

1-(4-Fluorophenyl)-2-methyl-2-aminopropane	CAS No 1200-27-7	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
SDS US (GHS HazCom 2012)	

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.